Kinetic

Power Up with
EP12-B Charging Cart

Tired of tangled cables and dead devices?

Meet the EP12-B Charging Cart – the smart, secure, and efficient way to charge and store up to 12 tablets or laptops at once! Designed for schools, offices, and shared spaces, this charging cart combines cutting-edge technology with user-friendly features to keep your devices organized and fully powered.

Features

12 Charging Ports
Charge up to 12 devices simultaneously with PD3.0 fast charging technology.

Smart Safety Features
Overload, overcurrent, short-circuit, and leakage protection for worry-free charging.

Quiet Operation
Equipped with a quiet fan for a peaceful environment.

LED Indicators
Monitor charging status at a glance with red (charging) and green (fully charged) lights.

Anti-Collision Design
Rounded edges and flame-retardant materials ensure safety and durability.

Ideal For

Schools & Classrooms
Keep student devices charged and secure.

Offices & Coworking Spaces
Streamline charging for shared workspaces.

Training Centers & Libraries
Organize and power multiple devices effortlessly.

Specifications

Model	EP12-B（60W）
Name	Charging cart (PD)
Capacity	12 charging ports
Overall size(W*D*H)	W 594 x D 475 x H 410(mm)
Packing size(W*D*H)	W 664 x D 536 x H 480(mm)
Device slots	W 22 x D 424 x H 317(mm)
Suitable size of devices	Up to 15.6 inch
Applicability	Tablet and laptop
Net weight	28kg
Gross weight	31kg
Main material	SPCC+ABS
Charging protocol	PD3.0
Intput	200V～240V,10A,50Hz/60Hz
Output	5V,3A；9V,3A;12V,3A;15V,3A；20V,3A (*12 Ports)
Equiped power	900W
Maximum output power	720W

Safety

Grounding protection	Support
Overload protection	Support
Overcurrent protection	Support
Short-circuit protection	Support
Leakage Protection	Support
Isolation protection	Support

Authentication

CE,FCC,ROHS,REACH,CA65, Safety inspection report

Facade Features

Curved cabinet shape	Support
180 degree door	*1
Electronic code lock	*1
Fans	*1
Door lock	*2
Circuit breaker	*1
Timer screen	*1
Flame retardant clapbord (V0)	*13

Operating Environment

Working environment temperature	0˚C ~ 45˚C
Working environment humidity	20% ~ 80%
Storage environment temperature	0˚C ~ 45˚C

Packing List

Charging cart	*1
charging cable（C-C）	*12
Door keys	*2
Power cord	*1
User Manual	*1
QC certificate	*1

Container Loading

20GP	148 pieces
40HQ	380 pieces

Warranty

Construction	5 years
Electronic	5 years